

Usine productrice Hersteller Manufacturer <b>Ugine</b> <b>Avenue Paul</b> <b>Girod</b> <b>73403 Ugine</b> <b>France</b>	<b>INSPECTION CERTIFICATE 3.1</b> <b>CERTIFICAT DE RECEPTION 3.1</b> <b>ABNAHMEPRUEFZEUGNIS 3.1</b> ----- <b>EN 10204 / 3.1</b>	<b>UGITECH</b> Providing special steel solutions
--	---	---

Numéro / Nummer / Number <small>Bu sertifika BİRÇELİK PASLANMAZ ÇELİK LTD. ŞTİ. ye aittir. Bu sertifika hiçbir koşulda KOPYALANAMAZ VEYA ÇOĞALTILAMAZ.</small>	Ordre de fab. / Auftrag / Prod. Order <small>Bu sertifika BİRÇELİK PASLANMAZ ÇELİK LTD. ŞTİ. ye aittir. Bu sertifika hiçbir koşulda KOPYALANAMAZ VEYA ÇOĞALTILAMAZ.</small>	N° coulée / Schmelzen Nr / Heat N° <b>023053</b>	N° lot MM / Chargen / Batch <small>Bu sertifika BİRÇELİK PASLANMAZ ÇELİK LTD. ŞTİ. ye aittir. Bu sertifika hiçbir koşulda KOPYALANAMAZ VEYA ÇOĞALTILAMAZ.</small>
---	--	---	--

Certification - Werkzeugnis - Certificate <b>AD 2000-MERKBLATT W0/TRD100</b> <b>Pressure Equipment Directive 97/23/EC</b> <b>ISO 9001</b> <b>ISO/TS 16949</b> <b>ISO 14001</b>	ISO 9100 ISO 9120	Marque d'usine Herstellerzeichen Supplier's Mark  Poinçon de l'expert Prufstempel Inspector's stamp 
---	----------------------	---

UGI 304 BAR DRAWN POLISHED SOLUT° ANNEALED & COLD WORKED H9ROUND 22,000MM LONG. 6,000 M +50,000MM -0,000MM Produit UGI 304 BARRE ETIRÉE POLIE HYPERTREMPÉ DÉF. À FROID H9ROND(E) 22,000MM LONG. 6,000M +50,000MM - Erzeugnisform UGI 304 STAB GEZOGEN POLIERT ABGESCHRECKT KALTVERFORMT H9RUND 22,000MM LONG. 6,000M +50,000MM - Product UGI 304 BAR DRAWN POLISHED SOLUT° ANNEALED & COLD WORKED H9ROUND 22,000MM LONG. 6,000M +50,000M	6
---	---

Client et/ou destinataire - Besteller und/oder Empfänger - Purchaser and/or Consigner <b>12672 BIRCELİK PASLANMAZ ÇELİK TIC</b>	N° de commande client - Kundebestellnummer - Purchase order number <b>9 order dtd 02.04.2010</b>
--	---

Norme de référence / Besugsnorm / Standard for reference <b>AISI 304 ;</b>
---

Spécification client / Kundenspezifikation / Customer's specification - . .
--

Nombre Stueckzahl Pieces Nbr	Profil Profile Shape	Dimension Ausmessung Dimension	Longueur Laenge Length	Poids Gewicht Weigh
1	RO	22,000 MM 21-1	6,000 21-2	1084 KG

Mode d'élaboration Erchmel zungsart Melting process EAF + AOD + CC	N° prélèvement Probenummer Test number	Demandé / Vorschrift / Required										
			42	43	44	45	46	47	48	49		
38	0GTU	39A	Min									
			Max									
			0,0800	1,0000	2,0000	10,0000	20,0000	0,0300	0,0450	0,1000		
			<small>Bu sertifika BİRÇELİK PASLANMAZ ÇELİK LTD. ŞTİ. ye aittir. Bu sertifika hiçbir koşulda KOPYALANAMAZ VEYA ÇOĞALTILAMAZ.</small>									
			coulée/ Schmelzen / Heat									
			0,0470	0,3400	1,1100	8,0800	18,1500	0,0210	0,0300	0,0840		
			Produit / Erzeugnisform/ Product									

Demandé / Vorschrift / Required	50	51	52	53	54	55	70	71	72	73	74	75
Min												
Max												
coulée/ Schmelzen / Heat												
Produit / Erzeugnisform/ Product												

Demandé / Vorschrift / Required	76	77	78	79	80	81	82	83	84	85	86	87
Min												
Max												
coulée/ Schmelzen / Heat												
Produit / Erzeugnisform/ Product												

The contents of the report are accurate and all test results and operations performed by UGITECH or its subcontractors are in compliance with the material specification and the specific applicable material requirements of ASME NCA-3800	<b>Ugine le 17.09.2010</b> L'agent Réceptionnaire de l'usine <small>Der Werkbesucherstempel</small>
---	---

We declare that the mentioned product is in compliance with the requirements of the contract and that, after checks and tests, it meets in all respects the specified requirements and applicable standards and regulations, except reservations or exceptions as listed in this declaration of conformity ; Document validated by electronic signature. Material manufactured in the REACH regulation respect.	<small>Bu sertifika BİRÇELİK PASLANMAZ ÇELİK LTD. ŞTİ. ye aittir. Bu sertifika hiçbir koşulda KOPYALANAMAZ VEYA ÇOĞALTILAMAZ.</small>
---	---